

.098"(2.50mm) pitch single row pin headers




CW2502 Series

- * Poles:2-12
- * Material:Insulator:NYLON UL 94V-0 Color Nature
- * Contact:0.64mm(.025") square pin,brass,tin plated
- * Mates with CH2502-XX series housing

Specifications




- * Current rating: 3A AC, DC
- * Voltage rating: 250V AC, DC
- * Temperature range: -25°C~+85°C
- * Insulation resistance: 1,000MΩ min.
- * Withstand voltage: 800V AC/minute
- * Applicable PC board thickness: .063" (1.6mm)



P.C. Board Layout




P/N: CW2502S-XX

Straight Angle



P/N: CW2502R-XX

Right Angle



CIRCUITS	PART NO.	DIMENSION in.(mm)		CIRCUITS	PART NO.	DIMENSION in.(mm)	
		A	B			A	B
2	CW2502X-02	0.098(2.50)	0.295(7.5)	8	CW2502X-08	0.689(17.50)	0.886(22.5)
3	CW2502X-03	0.197(5.00)	0.394(10.0)	9	CW2502X-09	0.787(20.00)	0.984(25.0)
4	CW2502X-04	0.295(7.50)	0.492(12.5)	10	CW2502X-10	0.886(22.50)	1.083(27.5)
5	CW2502X-05	0.394(10.00)	0.591(15.0)	11	CW2502X-11	0.984(25.00)	1.181(30.0)
6	CW2502X-06	0.492(12.50)	0.689(17.5)	12	CW2502X-12	1.083(27.50)	1.280(32.5)
7	CW2502X-07	0.591(15.00)	0.787(20.0)				